



## **Better than a Forced Air Heater**


- Better Efficiency
- No Blowing Air
- Warm floors / Dry Floors
- No Open Flame

# **Commercial / Industrial Quality**


- CSA Certified
- Natural Gas or Propane
- Straight or "U" Systems
- Direct Spark Ignition
- 100% Safety Lock Out
- Electronic Flame Monitoring
- Aluminized Steel Housing Powder Coated
- High Emisivity Radiant Tubing
- All Radiant Tubing Heat Treated Aluminized Steel for Corrosion Resistance
- Low Clearance to Combustibles
- 10 year Warranty on Radiant Tubes\*


<sup>\*</sup> See full warranty statement for details


Burner	Input Btu/hr	Emitter OD	"A" Dimension	Weight Lbs. (Straight System)	"B" Dimension	Weight Lbs. ("U" System)
0922R.NG/LP	40,000	3.5"	5'-0" / 10'-0"	75 / 105	10'0" / 19'-8"	90 / 115
0921R.NG/LP	45,000	3.5"	5'-0" / 10'-0"	75 / 105	10'0" / 19'-8"	90 / 115
0920R.NG/LP	50,000	3.5"	10'-0" / 14'-8"	105 / 130	19'-8" / 29'-10"	115 / 135
0919R.NG/LP	55,000	3.5"	10'-0" / 14'-8"	105 / 130	19'-8" / 29'-10"	115 / 135
0918R.NG/LP	60,000	3.5"	10'-0" / 14'-8" / 19'-8"	105 / 130 / 155	19'-8" / 29'-10" / 39'-4"	115 / 135 / 160




### **CLEARANCE TO COMBUSTIBLES**









PANEL REFLECTOR

PANEL REFLECTOR

STANDARD & DEEP REFLECTOR

STANDARD & DEEP REFLECTOR

Burner No.	Btu/Hr	Α	B1	С	D	E
0920R – 0922R NG/LP	40k to 50k	5"	44"	12"	12"	30"
0919R – 0918R NG/LP	55k to 60k	5"	50"	24"	12"	30"

Refer to Owners Manual for additional Clearance to Combustible information

#### **System Features**

Burner Assembly	Powder Coated For Superior Corrosion Resistance (Optional Stainless Steel)				
Gas Connection	1/2" NPT - Stainless Steel Flex Included With Each Burner - USA Only				
Heat Exchanger Tubing	Aluminized Steel (Optional - Stainless Steel)				
Exhaust flue O.D. (in.)	4"				
Reflectors	.024 Bright Aluminum (Optional .024 Stainless Steel)				
Ignition Control	Solid State, 3 Try Spark Ignition, 100% Shut-Off, Prepurge, 1 Hour Reset				
CSA Standards	USA - AGA Reg. 7-89 / ANSI Z21.86 (Current Standard) Canada - CSA 2.32 (Current Standard)				
Warranty	One Year On Ignition Controls & Electrical Components (Optional 3 Years) 10 Year on Radiant Tubes – Refer to Owners Manual for Details				

Installation Codes: COMBUSTION RESEARCH CORP. products are to be installed in accordance with local codes, laws and regulations and only by a contractor qualified in the installation and service of gas fired heating equipment.

For Further Information please contact your Independent distributor or the factory for details.

#### **Combustion Research Corporation**

2516 Leach Road Rochester Hills, MI 48309-3555

Telephone: 248.852.3611 Fax: 248.852.9165 Toll Free: 888.852.3611





#### www.combustionresearch.com

©2006 Combustion Research Corp. All rights reserved. No part of this work covered by the copyrights herein may be reproduced or copied in any form or by any means – graphic, electronic or mechanical, including photocopying, recording, taping or information storage and retrieval systems without written permission of Combustion research Corp.

Printed in U.S.A.

Bulletin - LIT.SE20060111